

# Pinnacle Series

## CLAD DOUBLE HUNG - Concealed Jambliner

### DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

		Operating						
Glass Size		16	20	24	28	32	36	40
		Width						
16	Height	35	35	35	35	35	35	35
20		35	35	35	35	35	35	35
22		35	35	35	35	35	35	35
24		35	35	35	35	35	35	35
26		35	35	35	35	35	35	35
28		35	35	35	35	35	35	35
30		35	35	35	35	35	35	35
32		35	35	35	35	35	35	35
34		35	35	35	35	35	35	35
36		35	35	35	35	35	35	35
		Oriel / Cottage DH						
24/36		35	35	35	35	35	35	35
		Oriel						
46/28		35	35	35	35	35	NA	NA
52/28		35	35	35	35	35	NA	NA
58/28		35	35	35	35	35	NA	NA

		Picture									
Glass Size		8	10	12	20	24	28	32	44	56	68
		Width									
42	Height	30	30	30	30	30	30	30	30	30	30
46		30	30	30	30	30	30	30	30	30	30
50		30	30	30	30	30	30	30	30	30	30
54		30	30	30	30	30	30	30	30	30	30
58		30	30	30	30	30	30	30	30	30	30
62		30	30	30	30	30	30	30	30	30	30
66		30	30	30	30	30	30	30	30	30	30
70		30	30	30	30	30	30	30	30	30	30

		Transom									
Glass Size		16	20	24	28	32	36	40	44	56	68
		Width									
8	Height	40	40	40	40	40	40	40	40	40	35
10		40	40	40	40	40	40	40	40	40	35
12		40	40	40	40	40	40	40	40	40	35
20		40	40	40	40	40	40	40	40	40	30
26		40	40	40	40	40	40	40	40	40	30
32		40	40	40	40	40	40	40	40	40	30

Note: Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum Frame Width	Minimum Frame Height	Maximum Frame Width	Maximum Frame Height
Operating			
1-9 3/8	2-8 3/4	3-9 3/8	6-8 3/4
Picture			
1-1 3/8	2-10 3/4	6-1 3/8	6-4 3/4
Transom			
1-9 3/8	1-0	6-1 3/8	3-0

# Pinnacle Series

## CLAD SINGLE HUNG RADIUS - Concealed Jambliner

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Segment Top Single Hung				
Glass Size		24	28	32
		Width		
22	Height	35	35	35
24		35	35	35
26		35	35	35
28		35	35	35
30		35	35	35
32		35	35	35
34		35	35	35
36		35	35	35

Round Top Single Hung				
Glass Size		24	28	32
		Width		
22	Height	35	35	35
24		35	35	35
26		35	35	35
28		35	35	35
30		35	35	35
32		35	35	35
34		35	35	35
36		35	35	35

Note: Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

# Pinnacle Series

## CLAD DOUBLE HUNG - DP UPGRADE - Concealed Jambliner

### DESIGN PRESSURE VALUES

Operating - DP Upgrade							
Glass Size	16	20	24	28	32	36	40
	Width						
16	Height	50	50	50	50	50	50
20		50	50	50	50	50	50
22		50	50	50	50	50	50
24		50	50	50	50	50	50
26		50	50	50	50	50	50
28		50	50	50	50	50	50
30		50	50	50	50	50	50
32		50	50	50	50	50	50
34		50	50	50	50	50	50
36		50	50	50	50	50	50
Oriel / Cottage DH - DP Upgrade							
24/36	50	50	50	50	50	50	50

Picture - DP Upgrade								
Glass Size	8	10	12	20	24	28	32	44
	Width							
42	Height	50	50	50	50	50	50	50
46		50	50	50	50	50	50	50
50		50	50	50	50	50	50	50
54		50	50	50	50	50	50	50
58		50	50	50	50	50	50	50
62		50	50	50	50	50	50	50
66		50	50	50	50	50	50	50
70		50	50	50	50	50	50	50

Transom - DP Upgrade										
Glass Size	16	20	24	28	32	36	40	44	56	68
	Width									
8	Height	50	50	50	50	50	50	50	50	50
10		50	50	50	50	50	50	50	50	50
12		50	50	50	50	50	50	50	50	50
20		50	50	50	50	50	50	50	50	50
26		50	50	50	50	50	50	50	50	50
32		50	50	50	50	50	50	50	50	50

Note: Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.